

## PLS-020A-3PPI



## PLS-020A-3PPI

World's smallest magnetic  
Level Sensor

### Electrical Characteristics @ 25 °

Contact form		A
Contact rating max.	W / VA	10
Switching voltage max.	VDC	180
	VAC	130
Switching current max.	A	0.7
Carry current max.	A	1
Breakdown voltage min.	VDC	200
Total resistance max.	mΩ	280

### Environmental Characteristics

Operating temperature	°C	-20 to +80
Storage temperature	°C	-30 to +80


### Mechanical Characteristics

Density of float typ.*	g / cm <sup>3</sup>	0.7
Recommended minimum gravity of medium	g / cm <sup>3</sup>	Density of float + 20%

\* in delivery condition

### Dimensions in mm

© PIC GmbH



### Features

- > Polypropylene housing
- > FDA test passed
- > typ. Load resistive
- > Customized types available

### Approvals



Contact PIC for Agency Ratings!

### Ordering Information

Packing Unit	20	pcs
Weight per piece	5.6	g
Weight per package	120	g

PLS-020A-3PPI




**PLS-020A-3PPI**

World's smallest magnetic  
Level Sensor

Material Information

	Material	Colour
Housing	PA	black
Cable	UL 1007, AWG 24, 4 mm stripped and tinned	white
Nuts	PA66, M8, 1 pc preassembled	white
Float	PP foam	white
Potting	PU / Epoxy	black
Sealing ring	Silicone	white

Operation View




Remarks

When mounted near ferromagnetic parts switching distance of PLS-020A-3PPI may vary.

Electromagnetical influences and magnetic fields may change the switching behaviour of the Level Sensor.

Mounting



When mounted stem up, operating functions are reversed.